

NKE 6214-NR deep groove ball bearings

Browse NKE 6214-NR deep groove ball bearings Categories in the Manufacturers Online Free. including . 184.15 mm da 147.803 mm Ca

da	184.15 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	379.425 mm
S	4.763 mm
ba	103.188 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	87.313 mm
Housing	SAFS 640
Bearing	22340 CCK/W33

Adapter sleeve assembly	SNW 140×7.1/4
Stabilizing ring	SR-0-40
Taconite seal	TER 666
End plug (suffix Y)	EPR 21
Max. speed for Taconite seal	425 r/min
P60°	669 kN
P90°	400 kN
P120°	249 kN
P150°	222 kN
P180°	267 kN
Pa	82.7 kN
Mass pillow block	431 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g