## NKE K 81244-MB thrust roller bearings

What is NKE K 81244-MB thrust roller bearings in 0.0 Inventory mechanical engineering? Manufacturing Service . Upload N/A Minimum Buy Quantity your CAD file for an instant.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REGAL BELOIT   |
|                           |  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 1.814  |
| EAN                       | 0662798251349  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | YW250  |
| Seals                     | Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Single Row   Spherical   High<br>Base   Wide Inner Race   Has<br>Trash Guard |

| Long Description                 | 2 Bolt Pillow Block; 1-3/4"<br>Bore; 2-1/8" Base to Center<br>Height; Set Screw Mount; Ball<br>Bear |
|----------------------------------|---|
| UNSPSC                           | 31171511  |
| Harmonized Tariff Code           | 8483.20.40.40   |
| Noun                             | Bearing   |
| Keyword String                   | Pillow Block  |
| Manufacturer Item Number         | 1001-05669  |
| Manufacturer Internal Number     | 25134   |
| Weight / LBS                     | 5.2   |
| Actual Bolt Center to Center     | 0 Inch   0Millimeter  |
| d                                | 1.75 Inch   44.45 Millimeter  |
| D                                | 1.937 Inch   49.2 Millimeter  |
| Bolt Spacing Maximum             | 6.25 Inch   158.75Millimeter  |
| Nominal Bolt Center to<br>Center | 5.8 Inch   146.5 Millimeter   |
| В                                | 2.125 Inch   53.98 Millimeter   |
| Bolt Spacing Minimum             | 5.375 Inch   136.525Millimeter  |