

NKE NJ218-E-TVP3+HJ218-E cylindrical roller bearings

Advance NKE NJ218-E-TVP3+HJ218-E cylindrical roller bearings is your source for quality 215.001 mm Da and accessories. shop online for 85.801 mm Ca home delivery or pick up in one of our 10000 . 101.6 mm da

da	101.6 mm
Da	215.001 mm
Ca	85.801 mm
A1	120.65 mm
A2	254 mm
S	4.763 mm
ba	61.913 mm
H	257.175 mm
H1	133.35 mm
H2	53.975 mm
J min.	336.55 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	77.787 mm
R2	30.163 mm
RG	1/2 NPT
PG	1/4 NPT
h	46.831 mm
Housing	SAW 524

Bearing	23224 CCK/W33
Adapter sleeve assembly	SNW 124×4
Stabilizing ring	SR-24-20
Taconite seal	TER 657
End plug (suffix Y)	EPR 14
Max. speed for Taconite seal	775 r/min
P60°	185 kN
P90°	111 kN
P120°	72.5 kN
P150°	66.7 kN
P180°	81.4 kN
Pa	27.4 kN
Mass pillow block	49.9 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	379.89 g