

# NKE NJ2211-E-TVP3+HJ2211-E cylindrical roller bearings

What are the N/A Minimum Buy Quantity dimensions of a NKE NJ2211-E-TVP3+HJ2211-E cylindrical roller bearings? 0.0 Inventory Manufacturing Service . Get Your Free, NSK Manufacturer Name Instant Quote

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | NSK  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 35   |
| Product Group             | B04311   |
| Internal Clearance        | C4-Extra Loose   |
| Mounting Method           | Adapter Mount  |
| Rolling Element           | Spherical Roller Bearing   |
| Bore Profile              | Tapered  |
| Cage Material             | Bronze   |
| Enclosure                 | Open   |
| Number of Rows of Rollers | Double Row   |
| Relubricatable            | Yes  |
| Withdrawal Sleeve         | AH2238 (Specify bore)  |
| Inch – Metric             | Metric   |
| Long Description          | 190MM Tapered Bore; 340MM Outside Diameter; 92MM Width; C4-Extra Loose Clearance; Adapter Mount; Dou |
| Other Features            | Order adapter or withdrawal sleeve or nut separately. Others may be available                        |

|                              |   |
|------------------------------|---|
| UNSPSC                       | 31171510  |
| Harmonized Tariff Code       | 84823080  |
| Noun                         | Bearing   |
| Keyword String               | Spherical   |
| Manufacturer Item Number     | 22238CAMKE4C4   |
| Weight / LBS                 | 35  |
| d                            | 7.48 Inch   190 Millimeter  |
| Adapter Part Number          | SNW3138 H3138 HA3138 HS3138<br>(Specify bore) Inch   H3138<br>(Specify bore) Millimeter |
| B                            | 3.622 Inch   92 Millimeter  |
| D                            | 13.386 Inch   340 Millimeter  |
| bore diameter:               | 190 mm  |
| maximum rpm:                 | 1200 RPM  |
| outside diameter:            | 340 mm  |
| operating temperature range: | Maximum of +200 °C  |
| overall width:               | 92 mm   |
| cage material:               | Brass   |
| bore type:                   | Tapered 1:12  |
| bearing material:            | Steel   |
| outer ring type:             | Not Split   |
| cage type:                   | Inner Ring Guided   |
| internal clearance:          | C4  |
| precision rating:            | RBEC 1 (ISO Class Normal)   |
| closure type:                | Open  |
| finish/coating:              | Uncoated  |
| lubrication hole type:       | Lubrication Groove & Hole   |
| outer ring width:            | 92 mm   |
| dynamic load capacity:       | 1140000 N   |

|                       |           |
|-----------------------|-----------|
| fillet radius:        | 4 mm      |
| static load capacity: | 1730000 N |
| series:               | 222       |