

NKE NJ2215-E-TVP3 cylindrical roller bearings

NKE NJ2215-E-TVP3 cylindrical roller bearings Product Brochures , Manufacturing 44 mm D Service . 22 mm d Get Your Free.

d	22 mm
D	44 mm
B	12 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.07 kg
Dynamic load, C	9.4 kN
Static load, C ₀	5.05 kN
Fatigue limit load, C _u	0.23 kN
f ₀	13.9
N _{lim} (grease)	10,000 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.76 Hz
Characteristic outer ring frequency, BPF ₀	3.59 Hz
Characteristic inner ring frequency, BPF _I	5.41 Hz
da min	26 mm
da max	26.5 mm

Da max	40 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.075
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	22MM Bore; 44MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.163

Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Bore	0.866 Inch 22 Millimeter
Outside Diameter	1.732 Inch 44 Millimeter