

NKE NJ2215-E-TVP3 cylindrical roller bearings

NKE NJ2215-E-TVP3 cylindrical roller bearings Product Brochures , Manufacturing 44 mm D Service . 22 mm d Get Your Free.

d	22 mm
D	44 mm
B	12 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.07 kg
Dynamic load, C	9.4 kN
Static load, C ₀	5.05 kN
Fatigue limit load, C _u	0.23 kN
f ₀	13.9
N _{lim} (grease)	10,000 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.76 Hz
Characteristic outer ring frequency, BPF ₀	3.59 Hz
Characteristic inner ring frequency, BRFI	5.41 Hz
da min	26 mm
da max	26.5 mm

Da max	40 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.075
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	22MM Bore; 44MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.163

Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Bore	0.866 Inch 22 Millimeter
Outside Diameter	1.732 Inch 44 Millimeter