

NKE NJ2215-E-TVP3+HJ2215-E cylindrical roller bearings

How do you find the NKE NJ2215-E-TVP3+HJ2215-E cylindrical roller bearings specification? Manufacturers 62 Outer Diameter (mm) Online 25x62x25.25 Size (mm) Free check☐

Size (mm)	25x62x25.25
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Width (mm)	25.25
d	25 mm
D	62 mm
T	25.25 mm
B	24 mm
C	20 mm
a	8.7 mm
r1 min.	1.5 mm
r2 min.	1.5 mm
Weight	0.378 Kg
Basic dynamic load rating (C)	61200 kN
Basic static load rating (C0)	64100 kN
(Grease) Lubrication Speed	6900 r/min
(Oil) Lubrication Speed	9100 r/min
Calculation factor (e)	0.30
Calculation factor (Y0)	1.10
Bore Type	Cylindrical Bore
Configuration	Single Row
Enclosure	Open

Bore Size	25 mm
Outside Diameter	62 mm
Width	25.3 mm
Fillet Radius/Chamfer	1.5 mm
r1	1.5 mm
Load Center	8.6 mm
Dynamic Load Rating	61,200 N
Static Load Rating	64,100 N
Limiting Speed – Grease	6,900 rpm
Limiting Speed – Oil	9,100 rpm
Constant e	0.30
Axial Load Factor Y0	1.10
Axial Load Factor Y1	2.00
da (min)	33.5 mm
db (max)	33 mm
Da (min)	52 mm
Db (min)	57 mm
S1 (min)	3 mm
S2 (min)	5 mm
Cone ra (max)	1.5 mm
Cup ra (max)	1.5 mm