

NKE NJ2220-E-TVP3+HJ2220-E cylindrical roller bearings

Request A Quote 0.0 Inventory For Your Special NKE NJ2220-E-TVP3+HJ2220-E cylindrical roller bearings Needs Today! N/A Minimum Buy Quantity Free Quotes. ISO 9001 certified.

| | |
|--------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 14 lb |
| EAN | 0053893778396 |
| Product Group | M06288 |
| Component Description | Take Up Bearing Only |
| Rolling Element | Tapered Roller Bearing |
| Housing Style | Unit Only – Half Round Top Angle |
| Mounting Method | Concentric Collar |
| Compatible Take Up Frame | Not Specified |
| Adjustment Travel Length | 0 |
| Housing Material | Cast Iron |
| Other Features | Double Row Double Collar Two Lip Seal Electrodeposition Coating With Set Screw |
| Inch – Metric | Metric |
| Long Description | Take Up Bearing Only; 45MM Bore; Tapered Roller Bearing; Unit Only – Half Round Top Angle; Concentri |
| UNSPSC | 31171533 |
| Harmonized Tariff Code | 8483.20.40.80 |

| | |
|--------------------------------------|----------------------------|
| Noun | Bearing |
| Keyword String | Take Up |
| Manufacturer Item Number | E-TTU-TRB-45MM |
| Weight / LBS | 14.23 |
| Slot to Slot Distance | 0 Inch 0 Millimeter |
| d | 1.772 Inch 45 Millimeter |
| Slot Width | 0 Inch 0 Millimeter |
| Shaft Size | 1.772 in |
| Shaft Size Type | Metric |
| UPC Code | 053893778396 |
| Dimension B | 3-1/2 in |
| Dimension H | 6-3/8 in |
| Dimension H1 | 5-3/16 in |
| Dimension H2 | 2.39 in |
| Dimension d1 | 3-7/16 in |
| Dimension A | 1-3/4 in |
| Dimension A1 | 1-3/4 in |
| Housing Width | 2-9/16 in |
| Dimension L | 6-1/2 in |
| Dimension L1 | 6 in |
| Dimension L2 | 3.4 in |
| e | 0.33 |
| X (if $F_a/F_r \leq e$) | 0.87 |
| Y (if $F_a/F_r \leq e$) | 2.64 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 3.18 |
| K Factor | 1.83 |
| C90 Dynamic Load Rating ¹ | 10300 lb |
| C0 Static Load Rating | 43000 lb |

| | |
|--|---|
| Fa-max Maximum Permissible Thrust Load ² | 2590 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ³ | 8400 lb |
| Max. Speed ⁴ | 3050 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |