

NKE NJ2226-E-TVP3 cylindrical roller bearings

NKE NJ2226-E-TVP3 cylindrical roller bearings 5 Bore Diameter (mm) Warehouse offers 16 Outer Diameter (mm) car parts and car accessories. We sell discount online as 5x16x5 Size (mm) well as cheap machinery parts.

Size (mm)	5x16x5
Bore Diameter (mm)	5
Outer Diameter (mm)	16
Width (mm)	5
d	5 mm
D	14 mm
D1	16 mm
B	5 mm
C	5 mm
r min.	0,2 mm
C1	1 mm
da min.	6,6 mm
da max	7,4 mm
Da max.	12,4 mm
ra max.	0,2 mm
Weight	3,9 Kg
Basic dynamic load rating (C)	1,33 kN
Basic static load rating (C0)	0,505 kN
(Grease) Lubrication Speed	39 000 r/min
Inventory	0.0
Manufacturer Name	NTN

Minimum Buy Quantity	N/A
Weight / Kilogram	0.004
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	5MM Bore; 14MM Outside Diameter; 5MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P
Other Features	16 MM Flange OD
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Bore	0.197 Inch 5 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	0.551 Inch 14 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
bore diameter:	5 mm
static load capacity:	1 kN
outside diameter:	14 mm
precision rating:	Not Rated
overall width:	5 mm

finish/coating:	Uncoated
bore type:	Round
bearing material:	Stainless Steel
closure type:	Double Shielded
outer ring width:	5 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.2 mm
internal clearance:	C0
maximum rpm:	46000 RPM
dynamic load capacity:	16 kN
series:	FL