## NKE NJ2314-E-MA6 cylindrical roller bearings

NKE NJ2314-E-MA6 cylindrical roller bearings manufacturer and global supplier of reliable ball and roller ... NKE NJ2314-E-MA6 cylindrical roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted 0.0 Inventory industries.

| Inventory                 | 0.0                      |
|---------------------------|--------------------------|
| Manufacturer Name         | REXNORD                  |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 12.167                   |
| EAN                       | 0793699901733            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 4                        |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Iron                |
| Expansion / Non-expansion | Expansion                |
| Mounting Bolts            | 5/8 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 6212U                    |
| Seals                     | Clearance Seal           |
| Housing Configuration     | 1 Piece Solid            |
| Inch — Metric             | Inch                     |
| Other Features            | Double Row               |

| Long Description              | 4 Bolt Pillow Block; 2-3/4"<br>Bore; 3-1/4" Base to Center<br>Height; Tapered Adapter Sleeve<br>Mou |
|-------------------------------|---|
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | ZAS6212F  |
| Manufacturer Internal Number  | 190173  |
| Weight / LBS                  | 26.8  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter   |
| Actual Bolt Center to Center  | 8.1 Inch   206Millimeter  |
| d                             | 2.75 Inch   69.85 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| В                             | 3.25 Inch   82.55 Millimeter  |
| D                             | 4.531 Inch   115.09 Millimeter  |