

NKE NJ2315-E-MA6 cylindrical roller bearings

are a few brands you will find in our inventory. Find NKE NJ2315-E-MA6 cylindrical roller bearings to see 40 mm d what's in stock!

d	40 mm
D	80 mm
B	18 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.37 kg
Dynamic load, C	29.1 kN
Static load, C ₀	17.8 kN
Fatigue limit load, C _u	0.81 kN
f ₀	14
N _{lim} (oil)	10,000 rpm
N _{lim} (grease)	8,700 rpm
Min operating temperature, T _{min}	-60 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.84 Hz
Characteristic outer ring frequency, BPF ₀	3.61 Hz
Characteristic inner ring frequency, BRF ₁	5.39 Hz
da min	46.5 mm
Da max	73.5 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.36
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 3 ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Nylon
Rolling Element	Ball Bearing
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row Deep Groove C3 Clearance
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open Enclosure; ABEC 3 ISO P6 Precision; Steel Ball
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Bore	1.575 Inch 40 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Width	0.709 Inch 18 Millimeter