

NKE NJ2326-E-TVP3+HJ2326-E cylindrical roller bearings

Enjoy High Margins 80x170x58 Size (mm) on Competitive 170 Outer Diameter (mm) Pricing.Great Wholesale Products at Low Costs.

| | |
|-------------------------------|------------|
| Size (mm) | 80x170x58 |
| Bore Diameter (mm) | 80 |
| Outer Diameter (mm) | 170 |
| Width (mm) | 58 |
| d | 80 mm |
| D | 170 mm |
| B | 58 mm |
| C | 58 mm |
| d2 | 104 mm |
| r1 min. | 2,1 mm |
| r2 min. | 2,1 mm |
| D1 | 148 mm |
| da min. | 92 mm |
| Da max. | 158 mm |
| ra max. | 2 mm |
| Weight | 6,1 Kg |
| Basic dynamic load rating (C) | 135 kN |
| Basic static load rating (C0) | 49 kN |
| Fatigue load limit (Pu) | 2,24 |
| Reference speed | 7000 r/min |
| Limiting speed | 5300 r/min |
| Calculation factor (e) | 0,37 |

| | |
|-------------------------|------|
| Calculation factor (kr) | 0,05 |
| Calculation factor (Y0) | 1,8 |
| Calculation factor (Y1) | 1,7 |