

# NKE NJ2340-E-M6+HJ2340-E cylindrical roller bearings

YOU'LL FIND AN EXTENSIVE SELECTION N/A Minimum Buy Quantity OF  
NKE NJ2340-E-M6+HJ2340-E cylindrical roller bearings FOR SALE.  
0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 17.706   |
| EAN                       | 0883450029278                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 7/8 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Triple Lip Viton                               |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 90MM Bore; 95MM Base to Center Height; Concentric Collar Mount; Spherical Rolle |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QAAPL18A090SN  |
| Weight / LBS                  | 45   |
| D                             | 5.18 Inch   131.572 Millimeter   |
| Bolt Spacing Minimum          | 9.25 Inch   234.95Millimeter   |
| Bolt Spacing Maximum          | 10.75 Inch   273.05Millimeter  |
| d                             | 3.543 Inch   90 Millimeter   |
| Nominal Bolt Center to Center | 10 Inch   254 Millimeter   |
| B                             | 3.74 Inch   95 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |