

NKE NJ2340-E-MA6+HJ2340-E cylindrical roller bearings

Advance NKE NJ2340-E-MA6+HJ2340-E cylindrical roller bearings is your source for 200 mm Da quality and accessories. shop online for home delivery 109.537 mm da or pick up in one of our 10000 .

| | |
|-------------------------|-----------------|
| da | 109.537 mm |
| Da | 200 mm |
| Ca | 62.789 mm |
| A1 | 120.65 mm |
| A2 | 165.1 mm |
| ba | 51.594 mm |
| H | 244.475 mm |
| H1 | 125.425 mm |
| H2 | 52.388 mm |
| L | 419.1 mm |
| R1 | 73.025 mm |
| R2 | 31.75 mm |
| RG | 3/8 NPT |
| PG | 1/4 NPT |
| h | 40.922 mm |
| Housing | SSAFS 026 KA |
| Bearing | 23026 CCK/W33 |
| Adapter sleeve assembly | SNW 3026×4.5/16 |
| Stabilizing ring | 2 x 38151-26 |
| Labyrinth ring | 2 x LOR 115 |
| End plug (suffix Y) | EPR 15 |

| | |
|--|----------------|
| Bearing limiting speed | 3600 r/min |
| P60° | 141 kN |
| P90° | 84.5 kN |
| P120° | 52.5 kN |
| P150° | 48 kN |
| P180° | 57.4 kN |
| Pa | 20.2 kN |
| Mass pillow block | 52.2 kg |
| Cap bolt | 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m |
| Cap bolt, SAE grade | 8 |
| Eye bolt | 2 x 3/8-16 UNC |
| Initial grease fill | 232.47 g |