

# NKE NJ305-E-TVP3 cylindrical roller bearings

Request A Quote For Your Special NKE NJ305-E-TVP3 cylindrical roller bearings Needs Today! Free Quotes. 160 mm Da ISO 9001 80.963 mm da certified.

da	80.963 mm
Da	160 mm
Ca	49.809 mm
A1	98.425 mm
A2	149.225 mm
S	4.763 mm
ba	40.481 mm
H	196.85 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.781 mm
RG	3/8 NPT
PG	1/8 NPT
h	38.1 mm
Housing	FSAFS 518
Bearing	22218 EK

Adapter sleeve assembly	SNW 18×3.3/16
Stabilizing ring	SR-18-15
Labyrinth ring	2 x LOR 188
PosiTrac Plus contact element	2 x B10724-188
End plug (suffix Y)	EPR 11
Max. speed for PosiTrac Plus seal	1800 r/min
P60°	157 kN
P90°	94.3 kN
P120°	59.6 kN
P150°	54.3 kN
P180°	64.9 kN
Pa	10.9 kN
Mass pillow block	30.4 kg
Cap bolt	1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g