

NKE NJ338-E-MA6 cylindrical roller bearings

NKE NJ338-E-MA6 cylindrical roller bearings, Units and Housings 110 mm da CAD models , Manufacturing Service . Get Your Free.

da	110 mm
db	123.825 mm
dc	106.375 mm
Da	240 mm
Ca	89.789 mm
A1	133.35 mm
A2	206.375 mm
ba	48.419 mm
H	287.337 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	63.5 mm
Housing	SAF 322

Bearing	1322 M
Lock nut	AN 22
Lock washer	W 22
Stabilizing ring	2 x SR-1622
Labyrinth ring (db shaft position)	LOR 121
PosiTrac Plus contact element (db shaft position)	B10724-122
Labyrinth ring (dc shaft position)	LOR 113
PosiTrac Plus contact element (dc shaft position)	B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1150 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	54.7 kN
Mass pillow block	59.9 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	765.45 g