

NKE NU2314-E-TVP3 cylindrical roller bearings

YOU'LL FIND 55x120x49.2 Size (mm) AN EXTENSIVE SELECTION 120 Outer Diameter (mm) OF NKE NU2314-E-TVP3 cylindrical roller bearings FOR SALE.

Size (mm)	55x120x49.2
Bore Diameter (mm)	55
Outer Diameter (mm)	120
Width (mm)	49.2
d	55 mm
D	120 mm
B	49.2 mm
C	49.2 mm
Angle (α)	30 °
r min.	2 mm
Weight	2.30 Kg
Basic dynamic load rating (C)	112 kN
Basic static load rating (C0)	86,5 kN
(Grease) Lubrication Speed	4000 r/min
Inventory	3.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	2.302
EAN	4991893605662
Product Group	B00152
Enclosure	Open
Flush Ground	No

Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	20 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	55MM Bore; 120MM Outside Diameter; 49.2MM Width; Open; No Flush Ground; Ball Bearing; Double Row of
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5311 BNLS
Weight / LBS	5.07
Outside Diameter	4.724 Inch 120 Millimeter
Bore	2.165 Inch 55 Millimeter
Width	1.937 Inch 49.2 Millimeter
Configuration	Double Row
Bore Type	Cylindrical Bore
Bore Size	55 mm
Fillet Radius/Chamfer	2 mm
Dynamic Load Rating	112,000 N
Static Load Rating	86,500 N
Limiting Speed – Grease	4,000 rpm

Limiting Speed – Oil	5,500 rpm
Radial Clearance	0.008 to 0.028 mm
da	65 mm110 mm
Dx	131.5 mm
ra	2 mm
Cy	6.5 mm