

NKE NU2316-E-M6 cylindrical roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all 65x140x33 Size (mm) your NKE NU2316-E-M6 cylindrical roller bearings needs – including routine maintenance, major repairs, warranty 65 Bore Diameter (mm) service, and equipment inspections.

Size (mm)	65x140x33
Bore Diameter (mm)	65
Outer Diameter (mm)	140
Width (mm)	33
d	65 mm
D	140 mm
B	33 mm
C	33 mm
r1 min.	2.1 mm
da min.	77 mm
Da max.	128 mm
ra max.	2 mm
Weight	2.45 Kg
Basic dynamic load rating (C)	62 kN
Basic static load rating (C0)	22,8 kN
(Grease) Lubrication Speed	4300 r/min
(Oil) Lubrication Speed	5300 r/min
Calculation factor (e)	0.23
Calculation factor (Y0)	2.9
Calculation factor (Y1)	2.8

Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-313X
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 3 Deg 1:12 Taper
Long Description	65MM Bore; Tapered Adapter Mount; 140MM Outside Diameter; 33MM Inner Race Width; 33MM Outer Race Wid
Inch – Metric	Metric
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Weight / LBS	5.40132
Outer Race Width	1.299 Inch 33 Millimeter
Bore	2.559 Inch 65 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Inner Race Width	1.299 Inch 33 Millimeter