

NKE NU248-E-MA6 cylindrical roller bearings

offers a NKE NU248-E-MA6 cylindrical roller bearings selection of Genuine at Wholesale Prices. 280x180x74 Size (mm) We are a NKE NU248-E-MA6 cylindrical roller bearings 280 Bore Diameter (mm) Certified Parts Retailer

| | |
|-------------------------------|------------|
| Size (mm) | 280x180x74 |
| Bore Diameter (mm) | 280 |
| Outer Diameter (mm) | 180 |
| Width (mm) | 74 |
| d | 180 mm |
| D | 280 mm |
| B | 74 mm |
| d2 | 209 mm |
| D1 | 251 mm |
| s1 | 15.1 mm |
| r1,2 – min. | 2.1 mm |
| da – min. | 186 mm |
| da – max. | 223 mm |
| Da – min. | 239 mm |
| Da – max. | 269 mm |
| Ca – min. | 2 mm |
| ra – max. | 2 mm |
| Basic dynamic load rating – C | 880 kN |
| Basic static load rating – C0 | 1340 kN |
| Fatigue load limit – Pu | 122 kN |
| Reference speed | 2000 r/min |

| | |
|-------------------------------|---------------|
| Limiting speed | 2600 r/min |
| Factor – k1 | 0.112 |
| Factor – k2 | 0.105 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| UNSPSC | 31171505 |
| Weight / Kilogram | 0 |
| EAN | 7316571144016 |
| Product Group | B04144 |
| d2 ≈ | 209 mm |
| D1 ≈ | 251 mm |
| s1 max. | 15.1 mm |
| r1,2 min. | 2.1 mm |
| Da min. | 239 mm |
| Da max. | 269 mm |
| Ca min. | 2 mm |
| ra max. | 2 mm |
| Basic dynamic load rating C | 880 kN |
| Basic static load rating C0 | 1340 kN |
| Fatigue load limit Pu | 122 kN |
| Misalignment factor k1 | 0.112 |
| Operating clearance factor k2 | 0.105 |
| Mass bearing | 16.5 kg |