## NKE NUP2212-E-MA6 cylindrical roller bearings

We work closely with our NKE NUP2212-E-MA6 cylindrical roller bearings manufacturing partners to bring the TIMKEN Manufacturer Name best value to 0.0 Inventory customers. N/A Minimum Buy Quantity

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.442   |
| EAN                       | 0883450026147                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Expansion                                      |
| Mounting Bolts            | 3/4 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22215  |
| Seals                     | Double Lip Viton                               |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch — Metric             | Inch   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

| Long Description                 | 2 Bolt Pillow Block; 2-15/16"<br>Bore; 3-1/8" Base to Center<br>Height; Concentric Collar Mount; |
|----------------------------------|--|
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.80  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer Item Number         | QAAP15A215SEC  |
| Weight / LBS                     | 28   |
| Nominal Bolt Center to<br>Center | 8.8 Inch   223 Millimeter  |
| Bolt Spacing Maximum             | 9.625 Inch   244.475Millimeter   |
| Actual Bolt Center to<br>Center  | 0 Inch   OMillimeter   |
| Bolt Spacing Minimum             | 7.875 Inch   200.025Millimeter   |
| D                                | 4.74 Inch   120.396 Millimeter   |
| d                                | 2.938 Inch   74.625 Millimeter   |
| В                                | 3.125 Inch   79.38 Millimeter  |
|                                  |  |