

NKE NUP224-E-M6 cylindrical roller bearings

Various 65x120x23 Size (mm) types and sizes 65,000 Bore Diameter (mm) to accommodate your NKE NUP224-E-M6 cylindrical roller bearings 120,000 Outer Diameter (mm) requirements.

Size (mm)	65x120x23
Bore Diameter (mm)	65,000
Outer Diameter (mm)	120,000
Width (mm)	23,000
d	65,000 mm
D	120,000 mm
B	23,000 mm
C	23,000 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.988
EAN	4547359568790
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal

Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	65MM Bore; 120MM Outside Diameter; 23MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6213LLUNR/2A
Weight / LBS	2.18
Outer Race Width	0.906 Inch 23 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter
Bore	2.559 Inch 65 Millimeter
bore diameter:	65 mm
static load capacity:	40000 N
outside diameter:	120 mm
precision rating:	ISO Class 0
overall width:	23 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	23 mm
snap ring included:	With Snap Ring
outer ring width:	23 mm
internal clearance:	CN

maximum rpm (grease):	3600 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1.5 mm
dynamic load capacity:	57500 N
manufacturer product page:	Click here