

NKE NUP320-E-MA6 cylindrical roller bearings

NKE NUP320-E-MA6 cylindrical roller bearings Product Brochures , 30x34x40 Size (mm) Manufacturing Service . Get Your 34 Outer Diameter (mm) Free.

Size (mm)	30x34x40
Bore Diameter (mm)	30
Outer Diameter (mm)	34
Width (mm)	40
d	30 mm
D	34 mm
B	40 mm
c1 min	0,1 mm
c2 min	0,8 mm
M	– mm
Weight	0,06 Kg
Basic dynamic load rating (C)	95 kN
c1 min.	0.1 mm
c1 max.	0.7 mm
c2 min.	0.8 mm
c2 max.	1.6 mm
$\alpha \pm 8$	20 °
Tolerance shaft	f7
Tolerance housing	H7
Basic dynamic load rating – radial direction C	95 kN
Basic static load rating – radial direction C0	300 kN
Specific dynamic load factor K	80 N/mm ²

Specific static load factor K_0	250 N/mm ²
Factor depending on material and bearing type K_M	480
Permissible sliding velocity v min.	0 m/s
Permissible sliding velocity v max.	2 m/s
Coefficient of friction μ min.	0.03
Coefficient of friction μ max.	0.25
Mass bushing	0.06 kg