

# NKX10-TV INA Cua 670 N / Fatigue limit load. axial 10x19x23mm Complex bearings

Bearing number	NKX10-TV
Size (mm)	10x19x23
Brand	INA
Bore Diameter (mm)	10
Outer Diameter (mm)	19
Width (mm)	23
$F_w$	10 mm
D	19 mm
C – 23 mm / Tolerance: -0,25	23 mm / Tolerance: 0.25
$C_1$ – 9 mm / Tolerance: -0,2	9 mm / Tolerance: 0.2
$C_2$	6.5 mm
$D_{1\ max}$	24.1 mm
$d_a$	19.7 mm
$d_w$	10 mm / Tolerance: E8
$r_{a\ max}$	0.3 mm
$r_{min}$	0.3 mm
	NAXK10TN / Designation to DIN 5429
m	34 g / Weight
$C_r$	7000 N / Dynamic load rating (radial)
$C_{0r}$	7800 N / Static load rating (radial)

$C_a$	10000 N / Dynamic load rating (axial)
$C_{0a}$	14000 N / Static load rating (axial)
$C_{ur}$	1310 N / Fatigue limit load. radial
$C_{ua}$	670 N / Fatigue limit load. axial
$n_G$	12400 1/min / Limiting speed
	IR7X10X16 / Suitable inner ring
Category	Thrust Roller Bearing
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.041
EAN	4012802732092
Product Group – BDI	B00234
Rolling Element	Combination – Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Polyamide
Precision Class	ABEC 1   ISO P0
Long Description	10MM Bore 1; 10MM Bore 2; 19MM Outside Diameter; 23MM Height; Combination – Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Polyamide Cage; ABEC 1   ISO P0; Roller Assembly plus Raceways

Inch – Metric	Metric
Category – BDI	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40
Noun	Bearing
Keyword String	Combination
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Item Number	NKX10TN
Weight / LBS	0.075
Bore 1	0.394 Inch   10 Millimeter
Overall Height with Aligning Washer	0 Inch   0 Millimeter
Bore 2	0.394 Inch   10 Millimeter
Outside Diameter	0.748 Inch   19 Millimeter
Height	0.906 Inch   23 Millimeter