

NKX15T2 NTN Nlim (grease) 6.200 rpm Complex bearings

dw	15 mm
rs min	0.3 mm
Dw	2 mm
Dw1	4.76 mm
Lw	9.8 mm
Lubrication hole on outer ring	Oui/Yes
k	2.5 mm
Precision class	P0
Mass	0.04 kg
Cr	8.25 kN
Ca	10.5 kN
C0r	10.2 kN
C0a	16.8 kN
Nlim (grease)	6.200 rpm
Nlim (oil)	8.800 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	23 mm
ras max	0.3 mm
Bearing number	NKX15T2
Brand	NTN
Bore Diameter (mm)	15
Outer Diameter (mm)	28
d	15 mm
Fw	15 mm

D	24 mm
D1	28 mm
C	23 mm
r min.	0.3 mm
C1	9 mm
da min.	23 mm
ra max.	0.3 mm
C2	6.5 mm
Weight	0.044 Kg
Dynamic load rating radial (C)	8.25 kN
Dynamic load rating axial (C)	10.5 kN
Static load rating radial (C0)	10.2 kN
Static load rating axial (C0)	16.8 kN
(Grease) Lubrication Speed	6200 r/min
Category	Roller Bearings
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.047
EAN	4547359126082
Product Group – BDI	B04144
bore diameter:	15 mm
static load capacity:	1040 kgf
outside diameter:	28 mm
maximum rpm:	8800 RPM
overall width:	23 mm
flanges:	No Flange
needle bearing type:	Machined Bearing with No Inner Ring

series:	NKX
closure type:	Open
lubrication hole type:	No Hole
dynamic load capacity:	840 kgf
precision rating:	Not Rated