

NKX15T2Z NTN r min. 0.3 mm

Complex bearings

dw	15 mm
rs min	0.3 mm
Dw	2 mm
Dw1	4.76 mm
Lw	9.8 mm
Lubrication hole on outer ring	Oui/Yes
k	2.5 mm
Precision class	P0
Mass	0.05 kg
Cr	8.25 kN
Ca	10.5 kN
C0r	10.2 kN
C0a	16.8 kN
Nlim (grease)	6.200 rpm
Nlim (oil)	8.800 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	23 mm
ras max	0.3 mm
Bearing number	NKX15T2Z
Brand	NTN
Bore Diameter (mm)	15
Outer Diameter (mm)	29
d	15 mm
Fw	15 mm

D	24 mm
D1	28 mm
D2	29 mm
C	23 mm
a	23.7 mm
r min.	0.3 mm
C1	9 mm
da min.	23 mm
ra max.	0.3 mm
C2	6.5 mm
Weight	0.048 Kg
Dynamic load rating radial (C)	8.25 kN
Dynamic load rating axial (C)	10.5 kN
Static load rating radial (C0)	10.2 kN
Static load rating axial (C0)	16.8 kN
(Grease) Lubrication Speed	6200 r/min
Category	Bearings
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.858
Product Group – BDI	B04144