

NKX15T2Z NTN r min. 0.3 mm

Complex bearings

| | |
|---------------------------------|-----------|
| dw | 15 mm |
| rs min | 0.3 mm |
| Dw | 2 mm |
| Dw1 | 4.76 mm |
| Lw | 9.8 mm |
| Lubrication hole on outer ring | Oui/Yes |
| k | 2.5 mm |
| Precision class | P0 |
| Mass | 0.05 kg |
| Cr | 8.25 kN |
| Ca | 10.5 kN |
| C0r | 10.2 kN |
| C0a | 16.8 kN |
| Nlim (grease) | 6.200 rpm |
| Nlim (oil) | 8.800 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 23 mm |
| ras max | 0.3 mm |
| Bearing number | NKX15T2Z |
| Brand | NTN |
| Bore Diameter (mm) | 15 |
| Outer Diameter (mm) | 29 |
| d | 15 mm |
| Fw | 15 mm |

| | |
|--------------------------------|------------|
| D | 24 mm |
| D1 | 28 mm |
| D2 | 29 mm |
| C | 23 mm |
| a | 23.7 mm |
| r min. | 0.3 mm |
| C1 | 9 mm |
| da min. | 23 mm |
| ra max. | 0.3 mm |
| C2 | 6.5 mm |
| Weight | 0.048 Kg |
| Dynamic load rating radial (C) | 8.25 kN |
| Dynamic load rating axial (C) | 10.5 kN |
| Static load rating radial (C0) | 10.2 kN |
| Static load rating axial (C0) | 16.8 kN |
| (Grease) Lubrication Speed | 6200 r/min |
| Category | Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.858 |
| Product Group – BDI | B04144 |