

# NKX25      INA      25x37x30mm

## Harmonized      Tariff      Code

### 8482.80.00.40      Complex

## bearings

Bearing number	NKX25
Size (mm)	25x37x30
Brand	INA
Bore Diameter (mm)	25
Outer Diameter (mm)	37
Width (mm)	30
$F_w$	25 mm
D	37 mm
C – 30 mm / Tolerance: -0,25	30 mm / Tolerance: 0.25
$C_1$ – 11 mm / Tolerance: -0,2	11 mm / Tolerance: 0.2
$C_2$	9.5 mm
$D_{1 \max}$	42.1 mm
$d_a$	37.7 mm
$d_w$	25 mm / Tolerance: E8
$r_{a \max}$	0.6 mm
$r_{\min}$	0.6 mm
	NAXK25 / Designation to DIN 5429
m	125 g / Weight
$C_r$	21300 N / Dynamic load rating (radial)

$C_{0r}$	30500 N / Static load rating (radial)
$C_a$	19600 N / Dynamic load rating (axial)
$C_{0a}$	37500 N / Static load rating (axial)
$C_{ur}$	5300 N / Fatigue limit load. radial
$C_{ua}$	1790 N / Fatigue limit load. axial
$n_G$	6000 1/min / Limiting speed
	IR20X25X20 / Suitable inner ring
Category	Thrust Roller Bearing
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.13
EAN	4012802732153
Product Group – BDI	B00234
Rolling Element	Combination – Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1   ISO P0

Long Description	25MM Bore 1; 25MM Bore 2; 37MM Outside Diameter; 30MM Height; Combination – Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1   ISO P0; Roller Assembly plus Raceways
Inch – Metric	Metric
Category – BDI	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40
Noun	Bearing
Keyword String	Combination
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Item Number	NKX25
Weight / LBS	0.276
Bore 2	0.984 Inch   25 Millimeter
Outside Diameter	1.457 Inch   37 Millimeter
Overall Height with Aligning Washer	0 Inch   0 Millimeter
Bore 1	0.984 Inch   25 Millimeter
Height	1.181 Inch   30 Millimeter