

NKX30 INA C0r 36000 N / Static load rating (radial) 30x42x30mm Complex bearings

Bearing number	NKX30
Size (mm)	30x42x30
Brand	INA
Bore Diameter (mm)	30
Outer Diameter (mm)	42
Width (mm)	30
F_w	30 mm
D	42 mm
C – 30 mm / Tolerance: -0,25	30 mm / Tolerance: 0.25
C_1 – 11 mm / Tolerance: -0,2	11 mm / Tolerance: 0.2
C_2	9.5 mm
$D_{1\ max}$	47.1 mm
d_a	42.7 mm
d_w	30 mm / Tolerance: E8
$r_{a\ max}$	0.6 mm
r_{min}	0.6 mm
	NAXK30 / Designation to DIN 5429
m	141 g / Weight
C_r	25500 N / Dynamic load rating (radial)
C_{0r}	36000 N / Static load rating (radial)

C_a	20400 N / Dynamic load rating (axial)
C_{0a}	42000 N / Static load rating (axial)
C_{ur}	6300 N / Fatigue limit load. radial
C_{ua}	2030 N / Fatigue limit load. axial
n_G	5000 1/min / Limiting speed
	IR25X30X20 / Suitable inner ring
Category	Thrust Roller Bearing
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.14
EAN	4012802732177
Product Group – BDI	B00234
Rolling Element	Combination – Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Long Description	30MM Bore 1; 30MM Bore 2; 42MM Outside Diameter; 30MM Height; Combination – Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller Assembly plus Raceways

Inch – Metric	Metric
Category – BDI	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40
Noun	Bearing
Keyword String	Combination
Manufacturer URL	http://www.ina.com
Manufacturer Item Number	NKX30
Weight / LBS	0.311
Bore 1	1.181 Inch 30 Millimeter
Height	1.181 Inch 30 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	1.181 Inch 30 Millimeter
Outside Diameter	1.654 Inch 42 Millimeter