

NKX70-Z INA 70x85x40mm Bore 1 2.756 Inch | 70 Millimeter Complex bearings

Category	Thrust Roller Bearing
BDI Inventory	1.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.728
EAN	4012802702132
Product Group – BDI	B00234
Rolling Element	Combination – Needle Roller and Thrust Ball Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Other Features	With Grease Retaining Cap
Long Description	70MM Bore 1; 70MM Bore 2; 85MM Outside Diameter; 40MM Height; Combination – Needle Roller and Thrust Ball Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller Assembly plus Raceways
Inch – Metric	Metric

Category – BDI	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.40
Noun	Bearing
Keyword String	Combination
Manufacturer URL	http://www.ina.com
Manufacturer Item Number	NKX70Z
Weight / LBS	1.103
Bore 2	2.756 Inch 70 Millimeter
Bore 1	2.756 Inch 70 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Height	1.575 Inch 40 Millimeter
Outside Diameter	3.346 Inch 85 Millimeter
Bearing number	NKX70-Z
Size (mm)	70x85x40
Brand	INA
Bore Diameter (mm)	70
Outer Diameter (mm)	85
Width (mm)	40
F_w	70 mm
D	85 mm
C – 40 mm / Tolerance: -0,25	40 mm / Tolerance: 0.25
C_1 – 18 mm / Tolerance: -0,2	18 mm / Tolerance: 0.2
C_2	11 mm
$D_{2 \max}$	96.5 mm

d_a	90.5 mm
d_w	70 mm / Tolerance: E8
$r_{a \max}$	1 mm
r_{\min}	1 mm
	NAXK70Z / Designation to DIN 5429
m	520 g / Weight
C_r	50000 N / Dynamic load rating (radial)
C_{0r}	92000 N / Static load rating (radial)
C_a	43000 N / Dynamic load rating (axial)
C_{0a}	127000 N / Static load rating (axial)
C_{ur}	15700 N / Fatigue limit load. radial
C_{ua}	6100 N / Fatigue limit load. axial
n_G	2400 1/min / Limiting speed
	IR60X70X25 / Suitable inner ring