

NKXR50 INA Overall Height with Aligning Washer 0 Inch | 0 Millimeter 50x62x35mm Complex bearings

Bearing number	NKXR50
Size (mm)	50x62x35
Brand	INA
Bore Diameter (mm)	50
Outer Diameter (mm)	62
Width (mm)	35
F_w	50 mm
D	62 mm
C – 35 mm / Tolerance: -0,25	35 mm / Tolerance: 0.25
C_1 – 14 mm / Tolerance: -0,2	14 mm / Tolerance: 0.2
C_2	10 mm
$D_{1\ max}$	70.2 mm
d_a	65.5 mm
d_w	50 mm / Tolerance: E8
$r_{a\ max}$	0.6 mm
r_{min}	0.6 mm
	NAXR50 / Designation to DIN 5429
m	268 g / Weight
C_r	43000 N / Dynamic load rating (radial)

C_{0r}	74000 N / Static load rating (radial)
C_a	62000 N / Dynamic load rating (axial)
C_{0a}	177000 N / Static load rating (axial)
C_{ur}	12700 N / Fatigue limit load. radial
C_{ua}	17400 N / Fatigue limit load. axial
n_G	4800 1/min / Limiting speed
n_B	1700 1/min / Reference speed
	IR45X50X25 / Suitable inner ring
Category	Thrust Roller Bearing
BDI Inventory	0.0
Manufacturer Name	SCHAEFFLER GROUP
Minimum Buy Quantity	N/A
Weight / Kilogram	0.27
EAN	4012802736076
Product Group – BDI	B00234
Rolling Element	Combination – Needle Roller and Thrust Roller Bearing
Self Aligning	No
Component Description	Roller Assembly plus Raceways
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0

Long Description	50MM Bore 1; 50MM Bore 2; 62MM Outside Diameter; 35MM Height; Combination – Needle Roller and Thrust Roller Bearing; Single Direction; Not Self Aligning; Not Banded; Steel Cage; ABEC 1 ISO P0; Roller Assembly plus Raceways
Inch – Metric	Metric
Category – BDI	Thrust Roller Bearings
UNSPSC	31171537
Harmonized Tariff Code	8482.80.00.80
Noun	Bearing
Keyword String	Combination
Manufacturer URL	http://www.ina.com
Manufacturer Item Number	NKXR50
Weight / LBS	0.591
Height	1.378 Inch 35 Millimeter
Bore 1	1.969 Inch 50 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	1.969 Inch 50 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter