

NMB R-1640HH deep groove ball bearings

Find the discount 25 Bore Diameter (mm) NMB R-1640HH deep groove ball bearings online 120 Outer Diameter (mm) you need . We offer ... If you check out our large selection of NMB R-1640HH deep groove ball bearings 25x120x82 Size (mm) once .

Size (mm)	25x120x82
Bore Diameter (mm)	25
Outer Diameter (mm)	120
Width (mm)	82
d	25 mm
H	120 mm
A	82 mm
A1	78.74 mm
A2	32 mm
A3	15 mm
d1	34 mm
D1	88 mm
D2	80 mm
D3	40 mm
Basic dynamic load rating – C	36.5 kN
Basic static load rating – C0	104 kN
Fatigue load limit – Pu	3.9 kN
Limiting speed, Preload class A	4500 r/min
Limiting speed for oil lubrication	2250 mm/min
Preload class A	3160 N
Preload class B	6320 N

Frictional moment, Preload class A	0.138 N·m
Frictional moment, Preload class B	0.24 N·m
Static Axial rigidity, Preload class A	1450 N/micron
Static Axial rigidity, Preload class B	1850 N/micron
Basic dynamic load rating C	36.5 kN
Basic static load rating C0	104 kN
Fatigue load limit Pu	3.86 kN
Attainable speed for preload class A	4500 r/min
Attainable speed for preload class B	2250 r/min
Frictional moment for preload class A	0.138 N·m
Frictional moment for preload class B	0.24 N·m
Static axial stiffnes for preload class A	1450 N/μm
Static axial stiffnes for preload class B	1850 N/μm
Mass cartridge unit	3.5 kg
Through hole diameter for attachment bolts N	9.2 mm
Pitch diameter of attachment bolt holes J	102 mm
Cartridge half diameter without flange J1	44 mm