

NMB RIF-5 deep groove ball bearings

How do I place an EMERGENCY 52x20x34 Size (mm) order for a NMB RIF-5 deep groove ball bearings that I want to pick up at a our store?

Size (mm)	52x20x34
Bore Diameter (mm)	52
Outer Diameter (mm)	20
Width (mm)	34
d	20 mm
D	52 mm
H	34 mm
D1	27 mm
B	8 mm
r1,2 – min.	1 mm
r3,4 – min.	0.3 mm
da	25 mm
Da – max.	36 mm
ra – max.	1 mm
rb – max.	0.3 mm
Basic dynamic load rating – C	34.5 kN
Basic static load rating – C0	60 kN
Fatigue load limit – Pu	2.2 kN
Reference speed	3200 r/min
Limiting speed	4500 r/min
Minimum load factor – A	0.018
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.317
EAN	7316577007209
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row
Long Description	20MM Bore 1; 27MM Bore 2; 52MM Outside Diameter; 34MM Height; Ball Bearing; Double Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	52305
Weight / LBS	0.698
Bore 1	0.787 Inch 20 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Bore 2	1.063 Inch 27 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Height	1.339 Inch 34 Millimeter

bore diameter:	20 mm
static load capacity:	60 kN
outside diameter:	52 mm
dynamic load capacity:	34.5 kN
overall width:	34 mm
maximum rpm:	4500 RPM
thrust bearing type:	Double-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	0.3 mm
separable or banded:	Separable
series:	523
precision rating:	ABEC 1 (ISO Class Normal)
D1 ≈	27 mm
r1,2 min.	1 mm
r3,4 min.	0.3 mm
Da max.	36 mm
ra max.	1 mm
rb max.	0.3 mm
Basic dynamic load rating C	34.5 kN
Basic static load rating C0	60 kN
Fatigue load limit Pu	2.24 kN
Minimum load factor A	0.018
Mass bearing (including seat washer where applicable)	0.33 kg