

# NSK 1305 K self aligning ball bearings

How do I 0.0 Inventory place an EMERGENCY order for a NSK 1305 K self aligning ball bearings that I want to pick up at a our store?

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 4.994  |
| EAN                       | 0883450025201                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 5/8 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22210  |
| Seals                     | Double Lip Nitrile Rubber                      |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 50MM Bore;<br>57.2MM Base to Center Height;<br>Concentric Collar Mount;<br>Spherical Rol |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QAAP10A050SB  |
| Weight / LBS                  | 13  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| B                             | 2.252 Inch   57.2 Millimeter  |
| D                             | 3.78 Inch   96 Millimeter   |
| Bolt Spacing Minimum          | 6 Inch   152.4Millimeter  |
| Bolt Spacing Maximum          | 7.125 Inch   180.975Millimeter  |
| Nominal Bolt Center to Center | 6.6 Inch   167 Millimeter   |
| d                             | 1.969 Inch   50 Millimeter  |