

# NSK 1305 self aligning ball bearings

What are the types 0.0 Inventory N/A Minimum Buy Quantity of NSK 1305 self aligning ball bearings ? Manufacturing Service . Get Your Free, Instant price, design review.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.522   |
| EAN                       | 0883450050098  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22219  |
| Seals                     | Double Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut  |
| Long Description          | 4 Bolt Pillow Block; 3-1/2" Bore; 3-3/4" Base to Center Height; V Lock Mount; Spherical Ro |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | QVPF19V308SEB                   |
| Weight / LBS                  | 43                              |
| B                             | 3.75 Inch   95.25 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| Nominal Bolt Center to Center | 10 Inch   254 Millimeter        |
| Bolt Spacing Maximum          | 10.875 Inch   276.225Millimeter |
| d                             | 3.5 Inch   88.9 Millimeter      |
| Bolt Spacing Minimum          | 8.875 Inch   225.425Millimeter  |
| D                             | 3.69 Inch   93.726 Millimeter   |