

NSK 160KBE43+L tapered roller bearings

Manufacturers of all 62x30x16 Size (mm) are represented in our partial list of clients. 62 Bore Diameter (mm) Contact Gary for a complete NSK 160KBE43+L tapered roller bearings list of clients and projects.

Size (mm)	62x30x16
Bore Diameter (mm)	62
Outer Diameter (mm)	30
Width (mm)	16
d	30 mm
D	62 mm
B	16 mm
d1	39.5 mm
D1	52.9 mm
r1,2 – min.	1 mm
da – min.	35.6 mm
Da – max.	56.4 mm
ra – max.	1 mm
Basic dynamic load rating – C	23.4 kN
Basic static load rating – C0	12.9 kN
Fatigue load limit – Pu	0.54 kN
Reference speed	24000 r/min
Limiting speed	15000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	13
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.19
EAN	7316571401416
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Polyamide
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove Reinforced Ball Set
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6206 ETN9
Weight / LBS	0.439
Outer Race Width	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter

bore diameter:	30 mm
static load capacity:	12.9 kN
outside diameter:	62 mm
finish/coating:	Uncoated
overall width:	16 mm
bearing material:	Steel
bore type:	Round
cage material:	Polyamide 66
closure type:	Open
fillet radius:	1 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	24000 rpm
snap ring included:	Without Snap Ring
weight:	0.4 lb
operating temperature range:	-40 to 212 °F °F
manufacturer product page:	Click here
dynamic load capacity:	23.4 kN
manufacturer upc number:	7316571401416
d1 ≈	39.5 mm
D1 ≈	52.9 mm
r1,2 min.	1 mm
da min.	35.6 mm
Da max.	56.4 mm
ra max.	1 mm
Basic dynamic load rating C	23.4 kN
Basic static load rating C0	12.9 kN
Fatigue load limit Pu	0.54 kN
Calculation factor kr	0.025
Calculation factor f0	13

Mass bearing	0.18 kg
--------------	---------