

NSK 210KBE31+L tapered roller bearings

The 55x72x9 Size (mm) online NSK 210KBE31+L tapered roller bearings parts store 72 Outer Diameter (mm) gives you immediate access to a selection of more than 1.4 million new, used, remanufactured.

Size (mm)	55x72x9
Bore Diameter (mm)	55
Outer Diameter (mm)	72
Width (mm)	9
d	55 mm
D	72 mm
B	9 mm
C	9 mm
rn	0,3 mm
r min.	0,3 mm
da min.	57 mm
da max	59 mm
Da max.	70 mm
ra max.	0,3 mm
Weight	0,083 Kg
Basic dynamic load rating (C)	8,8 kN
Basic static load rating (C0)	8,1 kN
(Grease) Lubrication Speed	8 700 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0
EAN	4547359006285
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	55MM Bore; 72MM Outside Diameter; 9MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.179
Bore	2.165 Inch 55 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter
bore diameter:	55 mm
precision rating:	ISO Class 0
outside diameter:	72 mm

finish/coating:	Uncoated
overall width:	9 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	9 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	8700 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	8700 RPM
dynamic load capacity:	8800 N
series:	68
static load capacity:	8100 N
manufacturer product page:	Click here