

NSK 23124L12CAM spherical roller bearings

Shop NSK 23124L12CAM spherical roller bearings huge online discount inventory. N/A Minimum Buy Quantity and Import machinery parts your car needs with Free 0.0 Inventory Shipping and Free Extended Warranty.

| | |
|---------------------------|----------------------------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 6.36 |
| EAN | 7316576664830 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Concentric Collar |
| Housing Style | 4 Bolt Round Flange Cartridge |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Expansion |
| Mounting Bolts | 1/2 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22211 |
| Seals | Trigard |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | With Pilot |
| Inch – Metric | Inch |

| | |
|------------------------------------|---|
| Long Description | 4 Bolt Round Flange Cartridge; 2-7/16" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1 |
| Other Features | Double Row Heavy Duty Open End With Set Screw |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | FYRP 2.7/16 |
| Weight / LBS | 14 |
| Bolt Spacing | 4.6 Inch 117 Millimeter |
| Cartridge Pilot Depth | 1 Inch 25.4 Millimeter |
| Cartridge Pilot Diameter | 5.512 Inch 140 Millimeter |
| d | 2.438 Inch 61.925 Millimeter |
| Nominal Bolt Circle Diameter Round | 6.5 Inch 165 Millimeter |
| D | 3.375 Inch 85.725 Millimeter |
| bore diameter: | 2-7/16 in |
| expansion type: | Non-Expansion Bearing (Fixed) |
| bolt center-to-center length: | 6.5000 in |
| seal type: | Contact/Lip |
| overall length/diameter: | 7.6250 in |
| overall depth: | 3-1/2 in |
| flange mounting type: | Four-Bolt Piloted |
| radial dynamic load capacity: | 33300 lb |
| bearing type: | Spherical Roller |

| | |
|------------------------------|-----------------------|
| radial static load capacity: | 41100 lb |
| housing construction: | Solid Flange Mount |
| operating temperature range: | Maximum of +110 °F °F |
| bore type: | Round |
| finish/coating: | Uncoated |
| duty type: | Standard Duty |
| lubrication type: | Lubrication Fitting |
| housing material: | Cast Iron |
| series: | 222 |
| locking device: | Set Screw |