

NSK 23160CAE4 spherical roller bearings

Browse NSK 23160CAE4 spherical roller bearings Categories in 80x125x22 Size (mm) the Manufacturers Online Free. 125 Outer Diameter (mm) including 80 Bore Diameter (mm) .

Size (mm)	80x125x22
Bore Diameter (mm)	80
Outer Diameter (mm)	125
Width (mm)	22
d	80 mm
D	125 mm
B	22 mm
C	22 mm
r min.	1,1 mm
da min.	86,5 mm
da max	91,5 mm
Da max.	118,5 mm
ra max.	1 mm
Weight	0,854 Kg
Basic dynamic load rating (C)	47,5 kN
Basic static load rating (C0)	40 kN
Reference speed	3 100 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.856
EAN	4547359004199

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 125MM Outside Diameter; 22MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0;
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6016LLU/2AS
Weight / LBS	1.892
Bore	3.15 Inch 80 Millimeter
Outside Diameter	4.921 Inch 125 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
bore diameter:	80 mm
precision rating:	ISO Class 0
outside diameter:	125 mm
finish/coating:	Uncoated
overall width:	22 mm
bearing material:	High Carbon Chrome Steel

bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	22 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	22 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	3100 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	6200 RPM
dynamic load capacity:	47500 N
series:	60
static load capacity:	40000 N
manufacturer product page:	Click here