

# NSK 23276CAKE4 spherical roller bearings

We work closely with our NSK 23276CAKE4 spherical roller bearings 50 Outer Diameter (mm) manufacturing partners to bring the 54x50x37 Size (mm) best value to customers.

Size (mm)	54x50x37
Bore Diameter (mm)	54
Outer Diameter (mm)	50
Width (mm)	37
d	50 mm
A	54 mm
A1	37 mm
H	26 mm
H1	57.2 mm
H2	22 mm
L	203 mm
J	157 mm
N1	18 mm
B	51.6 mm
s1	32.6 mm
Basic dynamic load rating – C	35.1 kN
Basic static load rating – C0	23.2 kN
Limiting speed	120 r/min
Limiting temperature – T	350 °C
Mass bearing unit	2.69 kg
Grub (set) screw – G2	M10x1

Hexagonal key size for grub screw – H	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.852
EAN	7316571382395
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 210-2F/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row   Standard Duty   Wide Inner Race   High Temperature Bearing with Graphite   Y Bearing
Long Description	2 Bolt Pillow Block; 50MM Bore; 57.2MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubri
UNSPSC	31171511

Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 50 TF/VA228
Weight / LBS	5.95
Bore	1.969 Inch   50 Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Actual Bolt Center to Center	6.2 Inch   157Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
Length Thru Bore	2.031 Inch   51.59 Millimeter
Base to Center Height	2.252 Inch   57.2 Millimeter
Nominal Bolt Center to Center	6.3 Inch   160 Millimeter
N	26 mm
Basic dynamic load rating C	35.1 kN
Basic static load rating C0	23.2 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Attachment bolts, recommended metric size G	16 mm
Bearing	YAR 210-2FW/VA228