

NSK 32BWK09-Y-2CP17-01 E tapered roller bearings

100% Authentic. 70x150x35 Size (mm) 70 Bore Diameter (mm) NSK 32BWK09-Y-2CP17-01 E tapered roller bearings Highest Quality. Certified Supplier.

Size (mm)	70x150x35
Bore Diameter (mm)	70
Outer Diameter (mm)	150
Width (mm)	35
d	70 mm
D	150 mm
B	35 mm
C	35 mm
ra1 max.	1 mm
Angle (α)	40 °
a	63,5 mm
r min.	2,1 mm
r1 min.	1,1 mm
2B	70 mm
da min.	82 mm
ra max.	2 mm
Db max	143 mm
Weight	5,22 Kg
Basic dynamic load rating (C)	186 kN
Basic static load rating (C0)	172 kN
(Grease) Lubrication Speed	3 500 r/min
Inventory	0.0

Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	5.22
EAN	4547359451948
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	2 (1 Pair)
Mounting Arrangement	Duplex-Back to Back
Inch – Metric	Metric
Long Description	70MM Bore; 150MM Outside Diameter; 70MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of B
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Outside Diameter	5.906 Inch 150 Millimeter
Bore	2.756 Inch 70 Millimeter
Width	2.756 Inch 70 Millimeter