

NSK 38KW01 tapered roller bearings

LET 1380H Cone Part Number OUR NSK 38KW01 tapered roller bearings 1300 Series EXPERTS GET YOU THE PARTS YOU NEED.

| | |
|---|---------------|
| Series | 1300 |
| Cone Part Number | 1380H |
| Design Units | Imperial |
| Cage Type | Stamped Steel |
| C1 – Dynamic Radial Rating (Two-Row, 1 million revolutions) ¹ | 22200 lbf |
| C90(2) – Dynamic Radial Rating (Two-Row, 90 million revolutions) ² | 5760 lbf |
| d | 0.8750 in |
| B – Cone Width | 0.7940 in |
| R – Cone Backface To Clear Radius ³ | 0.06 in |
| da – Cone Frontface Backing Diameter | 1.14 in |
| db – Cone Backface Backing Diameter | 1.24 in |
| Ab – Cage-Cone Frontface Clearance | 0.07 in |
| Aa – Cage-Cone Backface Clearance | 0.03 in |
| a – Effective Center Location ⁴ | -0.3 in |
| C90 – Dynamic Radial Rating (90 million revolutions) ⁵ | 3310 lbf |
| C1 – Dynamic Radial Rating (1 million revolutions) ⁶ | 12800 lbf |
| C0 – Static Radial Rating | 10900 lbf |
| Ca90 – Dynamic Thrust Rating (90 million revolutions) ⁷ | 1650 lbf |
| K – Factor ⁸ | 2 |

| |
|----------------------|
| Cg – Geometry Factor |
|----------------------|

| |
|--------|
| 0.0508 |
|--------|