

# NSK 52400/52618 tapered roller bearings

LET OUR NSK 52400/52618 tapered roller bearings EXPERTS GET YOU THE 55 Bore Diameter (mm) 90 Outer Diameter (mm) PARTS 55x90x49.6 Size (mm) YOU NEED.

Size (mm)	55x90x49.6
Bore Diameter (mm)	55
Outer Diameter (mm)	90
Width (mm)	49,6
d	55 mm
d2	45 mm
D	90 mm
T	49,6 mm
T2	29,8 mm
d3	90 mm
r min.	1 mm
r1 min.	0,6 mm
A1	32,5 mm
B	10 mm
D1	57 mm
R	72 mm
Da max.	72 mm
ra max.	1 mm
rb max.	0,6 mm
Weight	1,22 Kg
Basic dynamic load rating (C)	70 kN
Basic static load rating (C0)	159 kN

(Grease) Lubrication Speed	2000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.44
EAN	0029176029660
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row   With Aligning Seat
Long Description	45MM Bore 1; 57MM Bore 2; 90MM Outside Diameter; 49.6MM Height; Ball Bearing; Double Direction; Not
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	54211
Weight / LBS	2.44713
Height	1.953 Inch   49.6 Millimeter
Bore 1	1.772 Inch   45 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter

Overall Height with Aligning Washer	0 Inch   0 Millimeter
Bore 2	2.244 Inch   57 Millimeter
bore diameter:	45 mm
precision rating:	ABEC1, P0
outside diameter:	90 mm
static load capacity:	35500 lbf
overall width:	55 mm
dynamic load capacity:	15700 lbf
thrust bearing type:	Double-Direction
operating temperature range:	Maximum of +120 °C
outside diameter design:	Straight
maximum rpm:	3000 rpm
separable or banded:	Separable
cage material:	Steel Cage
race type:	Flat
series:	54200