

NSK 54244X thrust ball bearings

How do you find 136.525 mm da the NSK 54244X thrust ball bearings 289.999 mm Da specification? Manufacturers Online Free check

da	136.525 mm
Da	289.999 mm
Ca	113.817 mm
A1	158.75 mm
A2	288.925 mm
S	4.763 mm
ba	82.55 mm
H	336.55 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	52.388 mm
Housing	SAW 532
Bearing	23232 CCK/W33

Adapter sleeve assembly	SNW 132×5.3/8
Stabilizing ring	SR-32-0
Taconite seal	TER 129
End plug (suffix Y)	EPR 16
Max. speed for Taconite seal	560 r/min
P60°	226 kN
P90°	136 kN
P120°	85.9 kN
P150°	78.3 kN
P180°	94.3 kN
Pa	49.8 kN
Mass pillow block	109 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g