

# NSK 60/28DDU deep groove ball bearings

NSK 60/28DDU deep groove ball bearings Engineering 76.2 mm da Calculator , 150 mm Da 45.796 mm Ca Manufacturing Service . Get Your Free.

da	76.2 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	127 mm
ba	31.75 mm
H	182.166 mm
H1	95.25 mm
H2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
J1	53.975 mm
L	330.2 mm
N1	19.05 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	36.513 mm
Housing	FSAF 517
Bearing	1217 K
Adapter sleeve assembly	SNW 17×3

Stabilizing ring	2 x SR-1517
Labyrinth ring	2 x LOR 54
PosiTrac Plus contact element	2 x B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1950 r/min
P60°	61.4 kN
P90°	36.9 kN
P120°	23.1 kN
P150°	20.9 kN
P180°	25.4 kN
Pa	7.12 kN
Mass pillow block	16.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	218.29 g