

NSK 6008T1X deep groove ball bearings

Enjoy High 55 mm d Margins on Competitive Pricing.Great Wholesale Products at Low 120 mm D Costs.

| | |
|---|-----------|
| d | 55 mm |
| D | 120 mm |
| B | 29 mm |
| E | 106.5 mm |
| F | 70.5 mm |
| d1 | 77.7 mm |
| rs min | 2 mm |
| r1s min | 2 mm |
| Radial clearance class | CN |
| Mass (without HJ ring) | 1.52 kg |
| Dynamic load, C | 137 kN |
| Static load, C0 | 143 kN |
| Fatigue limit load, Cu | 17.4 kN |
| Nlim (oil) | 6,300 rpm |
| Nlim (grease) | 5,300 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.4 Hz |
| Characteristic rolling element frequency, BSF | 4.71 Hz |
| Characteristic outer ring frequency, BPF0 | 5.18 Hz |
| Characteristic inner ring frequency, BPF1 | 7.82 Hz |
| da min | 64 mm |
| da max | 69 mm |

| | |
|----------------------|---------------|
| dc min | 80 mm |
| Da max | 111 mm |
| ra max | 2 mm |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.52 |
| EAN | 4547359651737 |
| Product Group | B04144 |