

NSK 65BNR20HV1V angular contact ball bearings

How do you find the NSK 65BNR20HV1V angular contact ball bearings 42 Bore Diameter (mm) specification? Manufacturers 42x20x12 Size (mm) Online Free 20 Outer Diameter (mm) check

| | |
|-------------------------------|-------------|
| Size (mm) | 42x20x12 |
| Bore Diameter (mm) | 42 |
| Outer Diameter (mm) | 20 |
| Width (mm) | 12 |
| d | 20 mm |
| D | 42 mm |
| B | 12 mm |
| d2 | 24.65 mm |
| D2 | 37.19 mm |
| r1,2 – min. | 0.6 mm |
| da – min. | 23.2 mm |
| da – max. | 24.5 mm |
| Da – max. | 38.8 mm |
| ra – max. | 0.6 mm |
| Basic dynamic load rating – C | 10 kN |
| Basic static load rating – C0 | 5 kN |
| Fatigue load limit – Pu | 0.212 kN |
| Reference speed | 38000 r/min |
| Limiting speed | 19000 r/min |
| Calculation factor – kr | 0.025 |
| Calculation factor – f0 | 14 |
| Inventory | 0.0 |

| | |
|---------------------------------|---|
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.075 |
| EAN | 7316571823829 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 20MM Bore; 42MM Outside Diameter; 12MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove Low Friction NBR Seal |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 6004-2RSL |
| Weight / LBS | 0.158 |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 0.787 Inch 20 Millimeter |
| Outer Race Width | 0.472 Inch 12 Millimeter |

| | |
|-----------------------------|----------------------------|
| Outside Diameter | 1.654 Inch 42 Millimeter |
| d2 ≈ | 24.65 mm |
| D2 ≈ | 37.19 mm |
| r1,2 min. | 0.6 mm |
| da min. | 23.2 mm |
| da max. | 24.5 mm |
| Da max. | 38.8 mm |
| ra max. | 0.6 mm |
| Basic dynamic load rating C | 9.95 kN |
| Basic static load rating C0 | 5 kN |
| Fatigue load limit Pu | 0.212 kN |
| Calculation factor kr | 0.025 |
| Calculation factor f0 | 14 |
| Mass bearing | 0.069 kg |