

NSK 6828VV deep groove ball bearings

170 Million used NSK 6828VV deep groove ball bearings 72 Bore Diameter (mm) instantly searchable. Shop our large selection of parts based on brand, 72x50x12 Size (mm) price, description, and location. Order the with stock ...

Size (mm)	72x50x12
Bore Diameter (mm)	72
Outer Diameter (mm)	50
Width (mm)	12
d	50 mm
D	72 mm
B	12 mm
d1	57.95 mm
d2	56.9 mm
D2	66.04 mm
r1,2 – min.	0.6 mm
r3,4 – min.	0.3 mm
a	23.2 mm
da – min.	53.2 mm
db – min.	53.2 mm
Da – max.	68.8 mm
Db – max.	70 mm
ra – max.	0.6 mm
rb – max.	0.3 mm
dn	58.7 mm
Basic dynamic load rating – C	7.3 kN

Basic static load rating – C ₀	5.8 kN
Fatigue load limit – P _u	0.25 kN
Limiting speed for grease lubrication	22000 r/min
Limiting speed for oil lubrication	36000 mm/min
Ball – D _w	4.762 mm
Ball – z	29
G _{ref}	1.89 cm ³
Calculation factor – e	0.68
Calculation factor – Y ₂	1.41
Calculation factor – Y ₀	0.76
Calculation factor – X ₂	0.67
Calculation factor – Y ₁	0.92
Preload class A – G _A	43 N
Preload class B – G _B	86 N
Preload class C – G _C	260 N
Calculation factor – f	1.09
Calculation factor – f ₁	0.99
Calculation factor – f _{2A}	1
Calculation factor – f _{2B}	1.02
Calculation factor – f _{2C}	1.07
Calculation factor – f _{HC}	1
Preload class A	79 N/micron
Preload class B	102 N/micron
Preload class C	155 N/micron
r _{1,2} min.	0.6 mm
r _{3,4} min.	0.3 mm
d _a min.	53.2 mm
d _b min.	53.2 mm
D _a max.	68.8 mm

Db max.	70 mm
ra max.	0.6 mm
rb max.	0.3 mm
Basic dynamic load rating C	9.75 kN
Basic static load rating C0	9.65 kN
Fatigue load limit Pu	0.25 kN
Attainable speed for grease lubrication	22000 r/min
Attainable speed for oil-air lubrication	36000 r/min
Ball diameter Dw	4.762 mm
Number of balls z	29
Reference grease quantity Gref	1.89 cm ³
Preload class A GA	43 N
Static axial stiffness, preload class A	79 N/μm
Preload class B GB	86 N
Static axial stiffness, preload class B	102 N/μm
Preload class C GC	260 N
Static axial stiffness, preload class C	155 N/μm
Calculation factor f	1.09
Calculation factor f1	0.99
Calculation factor f2A	1
Calculation factor f2B	1.02
Calculation factor f2C	1.07
Calculation factor fHC	1
Calculation factor e	0.68
Calculation factor (single, tandem) Y2	0.87
Calculation factor (single, tandem) Y0	0.38
Calculation factor (single, tandem) X2	0.41
Calculation factor (back-to-back, face-to-face) Y1	0.92

Calculation factor (back-to-back, face-to-face) Y2	1.41
Calculation factor (back-to-back, face-to-face) Y0	0.76
Calculation factor (back-to-back, face-to-face) X2	0.67
Mass bearing	0.13 kg