

NSK 6907L11ZZ deep groove ball bearings

Advance 60 Bore Diameter (mm) NSK 6907L11ZZ deep groove ball bearings is your source for quality and accessories. shop online for home delivery or pick up 135 mm Da in one of our 10000 .

Bore Diameter (mm)	60
d	60 mm
Da	135 mm
s1	39.7 mm
A1	15 mm
B	65,1 mm
G	16 mm
J	160 mm
L	195 mm
N	19 mm
T	56,7 mm
A2	15 mm
A3	12 mm
J1	113.1 mm
Weight	4,9 Kg
Basic dynamic load rating (C)	52,7 kN
Basic static load rating (C0)	36 kN
Fatigue load limit (Pu)	1,53
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	4.9
EAN	7316570415490
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 212-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch – Metric	Metric
Long Description	4 Bolt Round Flange Cartridge; 60MM Bore; 160MM Bolt Circle; 113.1MM Bolt Spacing; 1 Piece Solid; Se
Other Features	Single Row Wide Inner Race Open End Has Flinger Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYC 60 TF
Weight / LBS	10.8

Bolt Spacing	4.453 Inch 113.1 Millimeter
Cartridge Pilot Depth	0.472 Inch 12 Millimeter
Nominal Bolt Circle Diameter Round	6.3 Inch 160 Millimeter
Length Thru Bore	2.563 Inch 65.09 Millimeter
Bore	2.362 Inch 60 Millimeter
Cartridge Pilot Diameter	5.315 Inch 135 Millimeter
Housing material	Cast iron
A	48 mm
B4	10 mm
Db	137.1 mm
RG	1/4-28 UNF
R1	24.5 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
Basic dynamic load rating C	52.7 kN
Basic static load rating C0	36 kN
Fatigue load limit Pu	1.53 kN
Limiting speed with shaft tolerance h6	3400 r/min
Mass unit	4.8 kg
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m

Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Bearing	YAR 212-2F
Housing	FYC 512