

NSK 7238 A angular contact ball bearings

Manufacturers of all are represented in our partial list 150 Outer Diameter (mm) of clients. Contact Gary for a complete NSK 7238 A angular contact ball bearings list of clients 190x150x20 Size (mm) and projects.

Size (mm)	190x150x20
Bore Diameter (mm)	190
Outer Diameter (mm)	150
Width (mm)	20
d	150 mm
D	190 mm
B	20 mm
d1	162.6 mm
D1	177.6 mm
r1,2 – min.	1.1 mm
da – min.	156 mm
Da – max.	184 mm
ra – max.	1 mm
Basic dynamic load rating – C	48.8 kN
Basic static load rating – C0	61 kN
Fatigue load limit – Pu	2 kN
Reference speed	6700 r/min
Limiting speed	4300 r/min
Calculation factor – kr	0.015
Calculation factor – f0	17.1
Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.42
EAN	7316576613005
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	150MM Bore; 190MM Outside Diameter; 20MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	61830 MA
Weight / LBS	3.12
Outer Race Width	0.787 Inch 20 Millimeter
Outside Diameter	7.48 Inch 190 Millimeter
Bore	5.906 Inch 150 Millimeter
bore diameter:	150 mm
static load capacity:	61 kN
outside diameter:	190 mm

precision rating:	Not Rated
overall width:	20 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Brass
closure type:	Open
outer ring width:	20 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	4300 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	48.8 kN
d1 ≈	162.6 mm
D1 ≈	177.6 mm
r1,2 min.	1.1 mm
da min.	156 mm
Da max.	184 mm
ra max.	1 mm
Basic dynamic load rating C	48.8 kN
Basic static load rating C0	61 kN
Fatigue load limit Pu	1.96 kN
Calculation factor kr	0.015
Calculation factor f0	17.1
Mass bearing	1.35 kg