

NSK 74551X/74846X cylindrical roller bearings

100% Authentic. NSK 74551X/74846X cylindrical roller bearings Highest Quality. Certified 35 Bore Diameter (mm) Supplier. 35x47x7 Size (mm)

Size (mm)	35x47x7
Bore Diameter (mm)	35
Outer Diameter (mm)	47
Width (mm)	7
d	35 mm
D	47 mm
B	7 mm
C	7 mm
a	1.3 mm
b	0.95 mm
f	0.85 mm
r min.	0.3 mm
r1 min.	0.3 mm
D1	45.7 mm
D2	49.8 mm
Weight	0.030 Kg
Basic dynamic load rating (C)	4,75 kN
Basic static load rating (C0)	3,8 kN
(Grease) Lubrication Speed	13000 r/min
Bore Type	Cylindrical Bore
Configuration	Single Row
Enclosure	Snap Ring Groove with Snap Ring

Bore Size	35 mm
Outside Diameter	47 mm
Width	7 mm
Fillet Radius/Chamfer	0.3 mm
r1	0.3 mm
Snap Ring Width	0.9 mm
Snap Ring Outside Diameter	49.8 mm
D1 (max)	45.7 mm
a (max)	1.3 mm
b (min)	1 mm
Dynamic Load Rating	4,750 N
Static Load Rating	3,800 N
Limiting Speed – Grease	14,000 rpm
Limiting Speed – Oil	16,000 rpm
Factor fo	16.4
Radial Clearance	0.006 to 0.020 mm
da (min)	37 mm
Da (max)	45 mm
Dx (min)	50.5 mm
ra (max)	0.3 mm
Cy (max)	1.8 mm